

# KOSTAL

INDUSTRIE ELEKTRIK



Smart  
connections.

Data sheet

INVEOR MP Modular

# INVEOR – "Smart connections." on five levels

### 1 The INVEOR

IP65 protection class  
Design without a fan up to 11 kW  
Cover level and internal space for e.g. the customer to mount a switch  
100% of connections can be plugged in (Harting plug HAN Q4/2, Quickon)  
Optional slots  
Brake module  
Robust and vibration-resistant housing concept  
Internal PTC brake resistor  
Functional safety

### 3 Operation and observation

Potentiometer  
M12 RS485 service interface  
Main switch  
MMI handheld controller  
MMI cover option  
Touch operating terminal  
PC software: KOSTAL INVERTERpc  
[www.kostal-industrie-elektrik.com/  
KOSTAL INVERTERpc](http://www.kostal-industrie-elektrik.com/KOSTAL_INVERTERpc)  
App: KOSTAL INVERTERapp

### 2 Communication

### 4 Motor adaptations

Robust and vibration-resistant adapter concept  
Motor adapter concept compatible with all commercially available motors  
Mechanics of motor adapter compatible with INVEOR M product group

### 5 Control process

Bluetooth®

Supports all synchronous reluctance, synchronous and asynchronous motors with maximum energy efficiency

FUNCTIONAL SAFETY

IEC 61800-9-2  
ECODISEIGN  
IE2  
ENERGY-EFFICIENT VARIABLE FREQUENCY DRIVES

IEC/EN 60034-30-1  
IE2 IE3 IE4 IE5  
IES SUPPORT SYNCHRONOUS MOTORS

RoHS  
2011/65/EU

CE

UL LISTED

## 400 V devices, technical data for INVEOR MP Modular

Size	A					B				C			D																
Recommended motor rating <sup>1)</sup> [kW]	0.55	0.75	1.1	1.5	2.2 LD <sup>5)</sup>	2.2	3	4	5.5 LD <sup>5)</sup>	5.5	7.5	11 LD <sup>5)</sup>	11	15	18.5	22	30 LD <sup>5)</sup>												
Supply voltage	3x200 V AC -10%...480 V AC +10% 280 V DC -10%...680 V DC +10% <sup>2)</sup>																												
Grid frequency	50/60 Hz ± 6%																												
Network configurations	TN / TT																												
Electrical data	Line current [A]	1.4	1.9	2.6	3.3	3.9	4.6	6.2	7.9	9.3	10.8	13.8	18.3	23.2	28.2	33.2	38.2	49.8											
	Rated current output eff. [IN at 4 kHz]	1.7	2.3	3.1	4	4.8	5.6	7.5	9.5	11	13	16.5	22	28	34	40	46	60											
	Min. brake resistance [Ω]	100					50					30																	
	Overload for 60 sec. [%]	150				110	150			110	150		110	150			110												
	Overload for 3 sec. [%]	200				150	200			150	200		150	200			150												
	Switching frequency	Auto regardless of temperature, 2 kHz, 4 kHz, 6 kHz, 8 kHz, 12 kHz, 16 kHz (factory setting 4 kHz)																											
	Output frequency	0 Hz – 599 Hz																											
	Nominal output apparent power [kVA]	1.06	1.43	1.93	2.49	2.99	3.49	4.68	5.92	6.86	8.11	10.29	13.72	17.46	21.2	24.94	28.6	37.41											
	Mains cycles of operation / restart	Unlimited <sup>3)</sup>											> 2 min.																
	DIN EN 61800-5 touch current	< 3.5 mA <sup>4)</sup>																											
Functions	Protective function	Overvoltage and undervoltage, I <sup>2</sup> t restriction, short-circuit, ground leak, motor and variable frequency drive temperature, stall prevention, blocking detection																											
	Software functions	Torque control <sup>6)</sup> , fixed frequencies, data record changeover, flying restart, motor current limit																											
Mechanical data	Housing	Two-part aluminium die-cast casing																											
	Dimensions [L x W x H] mm	233 x 153 x 120				270 x 189 x 140				307 x 223 x 181			414 x 294 x 232																
	Weight including adapter plate [kg]	3.9				5.0				8.7			21.0																
	Protection class [IPxy]	IP 65																											
	Cooling	Passive Cooling																											
	Climate class (DIN EN 60721-3-3)	3K3 (50°C)			3K3 (40°C)	3K3 (50°C)			3K3 (40°C)	3K3 (50°C)	3K3 (40°C)	3K3 (50°C)			3K3 (40°C)														
	Ambient temperature	-40 °C (non condensing) to +50 °C (without derating)				up to +40°C	-40 °C (non condensing) to +50 °C (without derating)			up to +40°C	-40 °C to +50 °C (with derating)	to +40°C	-40 °C to +50 °C (with derating)			to +40°C													
Environmental conditions	Storage temperature	-40 °C...+85 °C																											
	Altitude of the installation location	Up to 1000 m above sea level / over 1000 m with reduced performance (1 % per 100 m) / above 2000 m see operating manual																											
	Relative air humidity	≤ 96 %, condensation not permitted.																											
	Vibration class (DIN EN 60721-3-7) <sup>7)</sup>	3M7 (3g)																											
	EMC (DIN-EN-61800-3)	C2																											
	Energy efficiency class (EN 61800-9-2)	IE2																											
	Certificates and conformity	  																											

Technical data for 400 V devices INVEOR MP Modular (subject to technical changes)

<sup>1)</sup> Recommended motor rating (4-pole asynchr. motor) is given based on the 400 V AC supply voltage.

<sup>2)</sup> In compliance with the overvoltage category.

<sup>3)</sup> < 3 s may result in power failure/intermediate circuit undervoltage faults.

<sup>4)</sup> With 1A7 asynchronous motor, motor-mounted.


<sup>5)</sup> Low-duty devices with reduced output currents.

<sup>6)</sup> Only for synchronous and reluctance motors.

<sup>7)</sup> Installation- and application-related resonant frequencies can damage the devices.

# INVEOR MP Modular – Individually smart.

## MODULES



## POWER STACK

### Power stack, self-contained

Works without extra controller cards.



Model	Without IO module	With IO module 1
I/O interfaces <sup>1)</sup>	-	3 DI / 1 DO
STO input Sil 2 PLd	-	Option <sup>2)</sup>
Potentiometer on device	-	Option
MMI/MMI option	-	Option
Bluetooth	-	Option
Internal power supply	-	24 V DC, 100 mA short-circuit proof
External feed-in 24 V DC	-	only with STO or fieldbus option
Fieldbus integrated <sup>1)</sup>	Modbus RTU or CANopen	Modbus RTU and CANopen
Fieldbus option	-	Profinet, Sercos III optional, EtherCAT, EtherNet/IP
Brake module	-	Option
Main switch	-	Option


Technical data for INVEOR MP Modular 400 V devices (subject to technical changes)

<sup>1)</sup> Via M12 plug connector (optional)

# Variable frequency drive losses in accordance with EN 61800-9-2



INVEOR variable frequency drives meet the most stringent of energy efficiency requirements.



Device	Supply voltage [V]	Nominal current [A]	Absolute power loss [W] <sup>1)</sup> <sup>2)</sup>										Standby losses [W]	IE class		
			Relative losses [%] <sup>1)</sup> <sup>2)</sup> <sup>3)</sup>													
			Measurement (90; 100)	Measurement (50; 100)	Measurement (10; 100)	Measurement (90; 50)	Measurement (50; 50)	Measurement (10; 50)	Measurement (50; 25)	Measurement (10; 25)	Measurement (50; 10)	Measurement (10; 10)				
Size A 0.55 kW	400	1.7	24	24	27	22	20	25	24	25	5	5	IE2	IE2		
			2.3	2.2	2.5	2	1.9	2.4	2.2	2.3						
Size A 0.75 kW	400	2.3	29	28	32	23	21	28	25	27	5	5	IE2	IE2		
			2	1.9	2.2	1.6	1.5	2	1.7	1.9						
Size A 1.1 kW	400	3.1	35	30	38	27	26	31	26	28	5	5	IE2	IE2		
			1.8	1.6	2	1.4	1.3	1.6	1.4	1.4						
Size A 1.5 kW	400	4.0	45	39	46	31	27	36	25	31	5	5	IE2	IE2		
			1.8	1.6	1.8	1.3	1.1	1.4	1	1.2						
Size B 2.2 kW LD	400	4.8	56	51	54	39	36	40	35	33	5	5	IE2	IE2		
			1.9	1.7	1.8	1.3	1.2	1.3	1.2	1.1						
Size B 2.2 kW	400	5.6	61	60	65	46	38	48	37	42	7	7	IE2	IE2		
			1.7	1.7	1.9	1.3	1.1	1.4	1	1.2						
Size B 3.0 kW	400	7.5	83	62	80	54	38	58	28	51	7	7	IE2	IE2		
			1.8	1.3	1.7	1.2	0.8	1.3	0.6	1.1						
Size B 4.0 kW	400	9.5	107	80	98	66	51	70	31	58	7	7	IE2	IE2		
			1.8	1.4	1.7	1.1	0.9	1.2	0.5	1						
Size C 5.5 kW LD	400	11.0	137	117	122	71	67	70	50	56	7	7	IE2	IE2		
			2	1.7	1.8	1	1	1	0.7	0.8						
Size C 5.5 kW	400	13.0	149	114	125	69	52	76	44	70	7	7	IE2	IE2		
			1.8	1.4	1.5	0.9	0.6	0.9	0.5	0.9						
Size C 7.5 kW	400	16.5	203	157	166	98	75	95	58	78	7	7	IE2	IE2		
			2	1.5	1.6	0.9	0.7	0.9	0.6	0.8						
Size D 11.0 kW LD	400	22.0	323	226	244	151	123	133	80	99	7	7	IE2	IE2		
			2.4	1.6	1.8	1.1	0.9	1	0.6	0.7						
Size D 11.0 kW	400	28.0	249	222	245	148	133	140	101	109	18	18	IE2	IE2		
			1.4	1.3	1.4	0.8	0.8	0.8	0.6	0.6						
Size D 15.0 kW	400	34.0	314	279	298	181	163	173	122	134	18	18	IE2	IE2		
			1.5	1.3	1.4	0.9	0.8	0.8	0.6	0.6						
Size D 18.5 kW	400	40.0	381	333	347	211	189	202	140	152	18	18	IE2	IE2		
			1.5	1.3	1.4	0.8	0.8	0.8	0.6	0.6						
Size D 22.0 kW	400	46.0	485	398	392	247	189	276	197	194	18	18	IE2	IE2		
			1.7	1.4	1.4	0.9	0.7	1	0.7	0.7						
Size D 30.0 kW LD	400	60.0	710	579	581	360	284	317	125	243	18	18	IE2	IE2		
			1.9	1.5	1.6	1	0.8	0.8	0.3	0.6						

<sup>1)</sup> Loss values were determined at 4 kHz switching frequency

<sup>2)</sup> Loss values include 10% supplement in accordance with standard

<sup>3)</sup> Relative losses in relation to the device's rated apparent power

# KOSTAL

## Contact

KOSTAL Industrie Elektrik GmbH

Lange Eck 11

58099 Hagen

Deutschland

Telephone: +49 2331 8040-468

Fax: +49 2331 8040-602

[info-industrie@kostal.com](mailto:info-industrie@kostal.com)

[www.kostal-industrie-elektrik.com](http://www.kostal-industrie-elektrik.com)